

Secure Intercom

www.secureintercom.com.au

Division of Online Security PTY. LTD.



800B Intercom

Customer Assistance
VoIP Intercom Module



DO YOU WANT AN EVEN
HIGHER LEVEL OF FEATURES
AND PERFORMANCE?



Sales or Support Enquiries

Ph: +61 3 9008 7020

Ph: +1 617 8070 921

Email: sales@secureintercom.com

Head Office:

Unit 5 21-25 Redland Drive Mitcham, Victoria
Australia 3132

800B Intercom

101.5

Max: 104.3 Peak: 111.2

Quantity: Lp, F, Fast

Elapsed Time: 0h 0m 19.20s

20 40 60 80 100 120



- 10 Watt RMS Amplifier
- Audio Recorder Output
- PoE, 12-24V a.c. & d.c.
- Downlink Network Port
- 30 On-Board Messages
- Balanced Audio Circuits
- 4 Inputs, 3 Relay Outputs
- Standard SIP Architecture
- Remote Hardware Diagnostics



Feature	800B (PCB)	800MKL
Speaker	>101 dB SPL	>89 dB SPL
Audio	10 Watt RMS, <0.05% THD 2 to 16 Ohm Speaker Line Output (balanced)	1.35 Watt RMS, <10.0% THD 4 to 8 Ohm Speaker None
Messages	On-Board	SD Card
GPIOs	Optical Coupling 3 Relay Outputs	EOL Monitoring 2 Relay Outputs
Power Consumption	13 Watt (max.)	18 Watt (max.)
Dimension	117×77×22mm	124×88×43mm
Weight	90g	340g



Sales or Support Enquiries
 Ph: +61 3 9008 7020
 Ph: +1 617 8070 921
 Email: sales@secureintercom.com
 Head Office:
 Unit 5 21-25 Redland Drive Mitcham, Victoria
 Australia 3132